

INVERTER	PWM 50AMP/25Voc	GRID CHARGER
12V -850VA	0.85KW PV PANEL	Max. 15AMP



The “**LIGEN POWER**” inverter is a robust commercial-grade solution designed for small to medium-sized businesses, offices, and shops. With its advanced features and sturdy build, it ensures uninterrupted power supply during outages, enabling smooth operations.

Salient Features

- Efficient Power Performance: High efficiency with low energy consumption.
- CRGO Laminated Core: Premium quality for improved performance and durability.
- Pure Copper Transformer: Ensures optimal power conversion.
- Low No-Load DC Current: $0.7A \pm 0.3A$ for low idle consumption.
- High-Quality PCB: 70 Micron, high-grade design for reliability.
- Flexible Solar Integration: PV panel Voc up to 20V for varied solar setups.
- Consistent Output: Maintains a constant output power factor of 0.8, with 1000VA (800W max load) at a stable 220V.
- Advanced PWM Technology: Maximum tracking efficiency up to $\geq 85\%$, an enhanced version of PWM algorithm used to optimise solar energy conversion.
 - 1) Faster Response to Changing Conditions
 - 2) Improved Power Conversion
 - 3) Stable Performance

Generic Specification

Description	Details
Model No	LIGEN-INV850 - PWM
Product	Solar PWM PCU Inverter
Functionality	Works with Grid, Solar & Integrated LFP Battery
DSP Based	Less Components, small size less electricity bill more efficiency
Soft Start Features	Protects appliances at start-up
Usage	Reliable power backup for residential & commercial applications
Technology	Built-in PWM solar charge controller for optimized performance. Utilizes Sine Wave Technology for safe and efficient power delivery.
Battery Support	Internal 12.8V LIB Battery integrated with 4S1P BMS

Intelligent Processing

DSP technology enables advanced control algorithms for precise output regulation, adaptive learning for optimized battery management, and fault detection for enhanced reliability. Efficient power management and quick fault response ensure uninterrupted operation in offline applications.

Smart Display

Offers unique indications for mains status, Output status, system faults, Load status, Temperature status, Charging and battery status.

Operation Modes

Involves switching from mains power to battery power and Solar power during outages, ensuring uninterrupted supply to connected devices. Ideal for sensitive appliances like computers.

Protection Features

Includes MCB/Fuse for input mains protection and a bypass switch for direct main supply in case of inverter faults.

Grid Protection

AC input low and high voltage cut off protections in both, inverter and UPS modes

Noiseless Operation

Low harmonic distortion ensures quiet operation. This inverter prioritizes reliability, efficiency, and safety, making it an ideal choice for commercial establishments requiring dependable backup power solutions.

Technical Specification

Specification	Details
Model	850VA PWM PCU Inverter
Rated Power	850VA/680W (1-Phase Input 1-Phase Output)
Input Voltage (Battery Mode)	12.8V DC
BATTERY CHEMISTRY	Lithium iron phosphate (LFP)
BATTERY PACK	INTERNAL INTEGRATED WITH 4S1P BMS
BATTERY CAPACITY	100Ah
Grid Input Voltage (Vmp)	90V - 260V AC
Solar Input Voltage (Vmp)	17V – 22V DC
Solar Voc	≤ 25V DC
Maximum PV Connected	(50*Vmp) [Recommended ≤ 850W, Vmp @ 17V]
Solar Controller Type	PWM (Pulse Width Modulation)
Charging Modes	Solar, Grid, Solar + Grid [If Solar CHG ≤ (5.0A±0.5A)]
Output Waveform	Pure Sine Wave
Efficiency	> 90%
Max Solar Charging Current	50A±5A (Boost Mosfet based)
Max Grid Charging Current	15A±1A (CCCV)
Operation Logic for Charging	Solar Priority (By default)/Grid Priority
Output Voltage (Backup Mode)	220V AC ± 2%

Output Voltage (Grid Mode)	Same as Input
Output Frequency on Battery	50Hz $\pm$ 0.05Hz
Changeover Time	<8ms
Protection	Yes (Automatic Cut-off)
Protection Supported	Overload, Deep Discharge, Over Charge, Short Circuit, Over Temperature.
Over Load Capacity	>120%: 3 times auto reset, 4th time shut down >200% Output goes down
LED Indication	Solar (SR, BR, PR)
DISPLAY ON UPS/INVERTER	LOW BATT., BATT. VOLTAGE, CHG. CURRENT, CHG. MODE, AC IN, AC OUT, LOAD, OVERLOAD, TEMPERATURE, INV ON/OFF STATUS
Operating Temperature Range	-20°C to 65°C
Cooling Mechanism	Intelligent Fan Cooling
Cooling Fan Start/Stop	60°C or Load above 50%/50°C & Load below 50%
Audible Alarm	Yes
Bypass Feature	Manual

Solar Features

- Auto switchover between Solar and Main charging
- Zero drop solar charger (Max. 50A)
- Simultaneous charging through mains as well as solar panel
- Short charging time
- Long battery backup



Additional Features

- High Grade CRGO Laminated Pure Copper Transformer
- Zero Grid Power Consumption on Idle Stage
- No Load DC Current < 0.7A +/- 0.3A
- 70 Micron High Grade PCB
- Battery Grid Charging even at low grid Voltage
- Special charging algorithm to enhance battery life
- Intelligence charging adapts itself to low, high battery, more and less power cut areas, battery health condition.
- Forced Grid to Solar Mode Shifting Facility
- Constant Noise Free DSP Pure Sine Wave Output
- 4 Line Multifunctional LCD Front Panel display

- Intelligent true multi stage smart solar and grid charging (Bulk, Absorption, Float)
- High over load and surge load handling capacity
- MCB Short Circuit Protection for Grid Power
- Easy to operate
- No maintenance cost
- Fumeless

Physical Characteristics

Description	Status
Display	2 Line LCD Display
Dimensions – L x W x H (cm)	39.7 x 40.1 x 38.6

Warranty Information

Inverter	1 Years
Battery	6 Years
Coverage	Manufacturing defects & performance failures under normal usage

Solar Inverter v/s Power conditioning unit (PCU)

- The **Solar Inverter** is designed to give priority to **solar energy** for charging the battery. During the day, the battery primarily **charges using solar power**. However, if the **AC mains supply is available**, the system automatically switches to **bypass mode**, supplying power directly to the load while keeping the battery reserved. The stored **solar energy** remains unused until the **mains power is interrupted**, at which point the inverter seamlessly transitions to **battery mode**. This smart energy management approach helps in **maximizing solar utilization** while ensuring an **uninterrupted power supply**.*
- In a **Solar PCU**, battery charging is given **top priority** during the daytime when solar energy is available. The battery continues to **charge via solar power** until it reaches its **full charge voltage**. Once fully charged, the system switches to **inverter mode**, supplying power to the load directly from the battery, ensuring that **AC mains power remains unused** as long as solar energy is sufficient. If the battery gets **fully discharged**, the system automatically shifts to **mains mode**, where both the **load and battery charging** are managed through the AC supply. This setup ensures that **solar power is always utilized first**, while **mains power acts as a backup**, only stepping in when solar energy is completely depleted*

Amossys Portable Power LLP

Shed No-B4-05(FF), B4-06(FF), B4-07(FF) & B4-08(FF)

BIADA Industrial Area, Sikandarpur, Bihta Patna, Bihar – 801103

www.ligenpower.com